AD-A248 891

S COPY FOR REPRODUCTION PURPOSES

3E


Form Approved
OMB No. 0704-0188

conse, including the time for reviewing instructions, searching existing data sources, rmation. Send comments regarding this burden estimate or any other aspect of this justices Services, Directorate for information Operations and Reports, 128 Jeffers 1981, Paperwork Reduction Project (0704-0188), Washington, DC 20503

n in the factor of the second		Iget, Paperwork Reduction Project (0704-0188), Washington, DC 20503			
GLNCY USE ONLY (Leave blank)	2. REPORT DATE 20January 1992	3. REPORT TYPE	E AND DATES COVERED		
4. TITLE AND SUBTITLE A New Composite Roughness Surface Scattering Model			5. FUNDING NUMBERS		
6. AUTHOR(S) Gary S. Brown					
7. PERFORMING ORGANIZATION NAME Bradley Department of E Virginia Polytechnic Ir Blacksburg, Virginia 2	Electrical Engineer Astitute & State Un	-	8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P. O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSORING / MONITORING AGENCY REPORT NUMBER		
11. SUPPLEMENTARY NOTES The view, opinions and/author(s) and should no position, policy, or de 12a. DISTRIBUTION/AVAILABILITY STATE	t be construed as cision, unless so	an official D	epartment of the Army		
Approved for public rel	ease; distribution	unlimited.			

13. ABSTRACT (Maximum 200 words)

A new rough surface scattering theory which reduces to the composite surface scattering model is developed. It is based on the use of a normalized first order smoothing approximation in conjunction with the proper use of stationary phase to bring out the large scale surface shadowing. The theory provides the basis for improving on the conventional composite model.



14. SUBJECT TERMS Electromagnetic the	15. NUMBER OF PAGES 5		
method of smoothing	16 PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	UL.

A NEW COMPOSITE ROUGHNESS SURFACE SCATTERING MODEL

Final Report

bу

Gary S. Brown

20 January 1992

sponsored by

U.S. ARMY RESEARCH OFFICE

under

Grant Number DAAL03-89-K-0137

prepared by

Bradley Department of Electrical Engineerig

Virginia Polytechnic Institute & State University

Blacksburg, Virginia 24061-0111

The views, opinions, and/or findings contained in this report are those of the author and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION UNLIMITED

Scattering of electromagnetic fields by randomly rough, extended surfaces comprises an extremely difficult mathematical problem. In spite of this difficulty, basic understanding of the physics of the processes involved must be developed. This understanding is essential to the development of models for the prediction of the effects of rough surfaces on electromagnetic waves. The applications of such models are almost unbounded because rough surfaces are significantly more numerous, in nature, than smooth surfaces.

The mathematical difficulty of this problem has been a major hinderence in its solution. Recently, direct numerical solutions of the
basic integral equations governing the scattering processes have been
accomplished. However, these have been limited to one-dimensional or
corduroy surfaces and, even so, have been limited in their ability to
study and parameterize naturally occuring scattering situations. The
reason for this limitation is that the problem is still too large for
even the fastest and largest (in memory capacity) computers. Furthermore, the numerical solution of the basic equations is generating a
whole new set of difficulties which will take time and effort to
solve. Consequently, there is still a great need for an analytical
based solution for the full two-dimensional surface roughness problem.

One of the most successful scattering models to be developed for natural (terrain and ocean) surfaces is the so called composite roughness surface scattering model. In this model, the surface roughness spectrum is split into parts. The low (spatial) frequency part comprises spectral components whose wavelengths are large compared to the incident electromagnetic wavelength while the remaining part of the roughness spectrum encompasses the wavelengths which are comparable to or shorter than the electromagnetic wavelength. The key to the composite surface method is to use a low frequency approximate technique to analyze the scattering from the small wavelength features on the surface, a high frequency method for the long wavelength surface features, and some technique which properly estimates the degree to which these two scales of roughness mutually affect the scattering process. There is such a model available; it uses physical optics to predict the scattering from the low frequency part of the roughness spectrum and perturbation theory to estimate the scattering from the high frequency part. The interaction comes about through the tilting of the perturbation scattering solution by the low frequency surface spectral components. This interaction provides for the smooth transition between the perturbation and physical optics solutions.

The major advantage to this scattering model is that it shows how two asymptotic solutions can be combined to predict the scattering from a class of multi-scale surfaces. The disadvantage or drawback to the model is that it is not readily extended to surfaces which do not obey the assumptions of the model and it is not clearly obvious when the model starts to break down. The purpose of this research is to develop a new analytical scattering theory which is capable of reducing to the composite surface scattering model and can be extended to surfaces which do not obey the assumptions of the classical composite surface scattering model.

92-09250

The most significant result of this research is that we have been able to accomplish almost exactly what we set out to do. That is, we have developed an improved analytical scattering model that contains all of the physically intuitive features of the conventional composite surface scattering model and clearly shows how to systematically improve on it. This new theory has a number of crucial parts which are outlined below. A paper detailing the derivation of the theory is presently in preparation and will be submitted to a major journal.

The basic approach starts with the magnetic field integral equation for the current induced on a perfectly conducting rough surface by an incident field. The height dependent phase term in the source or Kirchhoff term of this equation is normalized out of transparent equation so that the method of smoothing can be applied to obtain an approximate solution of this equation. Without the normalization, first order smoothing (FOS) will fail as the surface height increases in magnitude relative to the electromagnetic wavelength. This failure of FOS will take place irrespective of the horizontal variability of the roughness and will, in fact, occur even if we have a randomly elevated planar surface. It is a consequence of the perturbative (in height) nature of the FOS approximation. The advantage and strength of the FOS approximation is that it provides a solution that does not require small surface height derivatives and this is a considerable advantage over conventional perturbative approximations.

The next part of the analysis comprises splitting the surface roughness height into the sum of a small scale component relative to the em wavelength and a large scale component. The small scale component is assumed to cover all surface features which have a wavelength that is comparable to or smaller than the em wavelength. The large scale component height covers all long wavelength (relative to the em wavelength) surface features. The intent of this spectral dichotomy is to use a theory which is appropriate to each spectral region since it is highly doubtful that any one approximate scattering theory will be adequate for the entire range of surface features.

We then split the infinite range integral in the integral equation into the sum of a finite range integral centered on the point of observation of the current and an infinite range integral covering the entire remainder of the z=0 plane. The extent of the finite range integral is such that it contains at least four wavelengths of the longest wavelength component in the small scale height. Thus, for example, if we split the spectrum at three times the em wavelength, the finite range integral would cover twelve em wavelengths. The criterion of taking the integration range to be four times the longest wavelength in the small scale height is based on insuring that the finite range integral contains sufficient small scale surface variation as to be representative of the small scale. It may be possible to make this range somewhat less than the above criterion.

The sum of the normalized Kirchhoff term and the finite range integral term are now used as the new source or Born term. Since the large scale surface has been constructed such that it is very smoothly undulating, we can solve for its effect on the scattering process by

iterating the integral equation (and its new Born term) and completing each integration via the method of stationary phase. It is very important to realize that stationary phase can be applied only after we have extracted the finite range integration from the integral we are to approximate via stationary phase. The reason for this is that we cannot apply stationary phase in a neighborhood of the point of observation (also the point of singularity in the normal derivative of the free space Green's function evaluated on the surface) because of the presence of the small scale surface structure. That is, stationary phase assumes that there is no structure on the surface that is smaller than or comparable to the em wavelength. Violation of this assumption makes no difference when the integration is well away from the point of obersvation; however, it is very important to satisfy this assumption when near to the point of singularity/observation.

Use of stationary phase leads to the introduction of a large scale dependent shadowing function which multiplies the normalized Kirchhoff term and the finite range integral term. However, the part of the equation that comprises the sum of these last two terms has as its solution the first order smoothing approximation or, more precisely, the normalized first order smoothing solution (NFOS) since it is the normalized equation that we are dealing with. Thus, our approximate solution of the normalized magnetic field integral equation is a large scale shadowed (normalized first smoothing) approximation for the small scale structure.

Reintroduction of the large scale dependent phase factor leads to a tilting effect of the underlying large scale surface. In short, our theory contains all of the conventional composite surface scattering model features. However, it also shows how one goes about going beyond the limitations of this model. For example, if there are large scale curvature effects that must be accounted for, our theory shows how they come into play in both the large scale solution and the small scale scattering. Hence, our theory, while still requiring a good deal more numerical work, satisfies nearly all of the goals of our original research proposal.

LIST OF ALL PUBLICATIONS AND TECHNICAL REPORTS

Gary S. Brown, "A new approach to the analysis of rough surface scattering," IEEE Transactions on Antennas & Propagation, Vol 39, No. 7, pp. 943-948, July, 1991.

Gary S. Brown, "Clutter modeling for the real enviornment: what are the problems?," Proceedings of the International Meeting on Detection, Discrimination, and Classification of Targets in Clutter, USA Missile Command, Huntsville, AL, in press.

LIST OF ALL PARTICIPATING SCIENTIFIC PERSONNEL

A.M. Koutoumbas, Graduate Research Assistant David A. Kapp, Graduate Research Assistant Kenneth W. Eure, Graduate Research Assistant Gary S. Brown, Professor, Pl

Accept Andrew NTIS 100 1 DID BAL U. a. a. Jakasa

> Ву [].

REPORT	OF	INVENTIONS	(BY	TITLE	ONLY):				
None									
BIBLIOGRAPHY:									
None									
	= .								
APPEND	IXES	5 :							
None									